



**SPECIFICATIONS:**

RATED CAPACITY — 600,000 IN LBS & 750,000 IN LBS.  
 OUTPUT @ RATED CAP — 2.0 MV/V NOM  
 BRIDGE RESISTANCE — 350 Ω

④ 13 3/4 DIA - 8 HOLES EQUALLY SPACED  
 BOTH FLANGES

REV. NO.	PART NO.	DESCRIPTION	RENO.
<b>OUTSIDE DIMENSIONS FLANGED REACTION TORQUE SENSOR</b>			
SCALE: FULL			
DATE: 8-8-65			
DRAWN BY: D.A. ANDREWS		JOB NO: 2285	
TOLERANCE ON FRACTIONS: 1/16" TOLERANCE ON DRILLED HOLES: ±.001			
TWO PLACE DECIMALS: ±.002 REMOVE ALL BURRS & SHARP EDGES			
THREE PLACE DECIMALS: ±.005 DIMENSION LIMITS WELD AFTER PLATING			
ANGLES: 1/16" SURFACE FINISH: 125			
UNLESS OTHERWISE SPECIFIED:			
<b>LEBOW ASSOCIATES, INC.</b>			
D-2115-D			

A ADDED 8/15/65  
 REV. NO. REVISION DATE

REF. D-12774