


AMP (NS) 4-COND, 6-PIN	
PIN	DESIGNATION
A	(+) SUPPLY
B	SUPPLY RETURN
C	(-) OUTPUT
D	(+) OUTPUT
E	N/C
F	N/C

IF THIS IS A PAPER COPY IT IS UNCONTROLLED. VERIFY REVISION BEFORE USE.

PROPRIETARY RIGHTS NOTICE: THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE PERMISSION OF HONEYWELL.

UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS IN INCHES. INTERPRET PER ASME Y14.100-2000 OTHER HONEYWELL STDS MAY APPLY. ALL FILLETS & CORNERS .005R MAX DEBURR & BREAK SHARP CORNERS			-	INITIAL RELEASE TO PRODUCTION	-	-	-
			REV	DESCRIPTION	REV BY	CHK BY	APV BY
AUTOCAD			DRW: EPSTEIN 4/30/2003	CHK: VICARS 5/2/2003	MFG: - XX/XX/XX	ENG: VICARS 05/09/2006	
REV HIST			 HONEYWELL SENSOTEC 2080 ARLINGATE LANE COLUMBUS, OHIO 43228 <a href="http://www.honeywell.com/sensing">www.honeywell.com/sensing</a>				
DATABASE VERIFIED:	N/A	N/A					
PLOT FILE VERIFIED:	N/A	N/A					
CATALOG VERIFIED:	N/A	N/A					
CATALOG REFERENCE:							
			EXTERNAL WIRING CODE AMP (NS) 6PIN, 4-COND				
			CODE IDENT NO. 51518		DOCUMENT NUMBER		
			SHEET 1 OF 1		SIZE A		001-0686-00