



SPECIFICATIONS

AVAILABLE RANGES: 250, 500, 1000 lb
 SUPPLY: 10 VDC
 OUTPUT: 2 mV/V
 STATIC ERROR BAND: \pm .02% F.S.
 NONLINEARITY: \pm .02% F.S.
 HYSTERESIS: \pm .02% F.S.
 COMPENSATED TEMPERATURE: 30°F TO 130°F
 TEMPERATURE EFFECT:
 ON ZERO: \pm .0008% F.S./°F
 ON SPAN: \pm .0008% Rdg./°F
 BRIDGE RESISTANCE: 350 Ohm NOMINAL
 CASE MATERIAL: STAINLESS STEEL

WIRING CODE

PIN	DESIGNATION
A	(+)EXCITATION
B	(+)OUTPUT
C	(-)OUTPUT
D	(-)EXCITATION
E	N/C
F	N/C

IF THIS IS A PAPER COPY IT IS UNCONTROLLED. VERIFY REVISION BEFORE USE.

PROPRIETARY RIGHTS NOTICE: THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE PERMISSION OF HONEYWELL.

UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS IN INCHES. INTERPRET PER ASME Y14.100-2000 OTHER HONEYWELL STDS MAY APPLY. ALL FILLETS & CORNERS .005R MAX DEBURR & BREAK SHARP CORNERS	-	INITIAL RELEASE TO PRODUCTION	-	-	-
	REV	DESCRIPTION	REV BY	CHK BY	APV BY
	DRW: DEITRICK	CHK: GAINES	MFG: -	ENG: WOODBURN	
	01/20/2005	01/21/2005	-	01/21/2004	

REV HIST	DO NOT SCALE	<p>HONEYWELL SENSOTEC 2080 ARLINGATE LANE COLUMBUS, OHIO 43228 www.honeywell.com/sensing</p>
	.X \pm .2	
	.XX \pm .02	
	.XXX \pm .010	
CODE IDENT NO. 51518		DOCUMENT NUMBER
SHEET 1 OF 1	SIZE A	000-8587-00

OUTLINE DRAWING, MODEL 47, STD
 \varnothing 4.13, 5/8-18 UNF