



WIRING CODE

6 COND. SUBMERSIBLE, 4-20 mA, 3 WIRE AMP

COLOR	DESIGNATION
RED	(+)SUPPLY (+22-32 VDC)
BROWN	OUTPUT COMMON
GREEN	SUPPLY RETURN
ORANGE	(+)OUTPUT (4-20 mA)
BLUE	SHUNT CAL 1
YELLOW	SHUNT CAL 2

NOTE : INTERCONNECTING SHUNT CAL 1 AND SHUNT CAL 2 PROVIDES 80% FULL-SCALE OUTPUT FOR QUICK CALIBRATION

SPECIFICATIONS

- 1.AVAILABLE RANGE : 0-25" THRU 0-1000"H2O OR 0-1 THRU 0-50 PSIG
- 2.ACCURACY : +/- 0.1%
- 3.OUTPUT : CURRENT (3 WIRE) AMPLIFIER
- 4.SUPPLY : 22 TO 32 VDC
- 5.COMP. TEMP : 60-160 DEG.F
- 6.COMP. TEMP ERROR
 ZERO : +/-0.0025 % fs/DEG.F
 SPAN : +/-0.0025 % fs/DEG.F
- 7.WETTED MATERIAL : 17-4 PH SS

IF THIS IS A PAPER COPY IT IS UNCONTROLLED. VERIFY REVISION BEFORE USE.

PROPRIETARY RIGHTS NOTICE: THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE PERMISSION OF HONEYWELL.

UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS IN INCHES. INTERPRET PER ASME Y14.100-2000 OTHER HONEYWELL STDS MAY APPLY. ALL FILLETS & CORNERS .005R MAX DEBURR & BREAK SHARP CORNERS		A	INITIAL RELEASE TO PRODUCTION	BNK		
AUTOCAD		REV	DESCRIPTION	REV BY	CHK BY	APV BY
REV HIST		DRW:	BNK 08/15/2008	CHK:	-	MFG: xx/xx/xx
DO NOT SCALE		ENG:	-	xx/xx/xx		
.X		HONEYWELL SENSOTEC 2080 ARLINGATE LANE COLUMBUS, OHIO 43228 www.honeywell.com/sensing				
±.2						
.XX						
±.02						
.XXX		MODEL LL-V STD.PRODUCT				
±.010		5 THRU 100 PSI				
		CODE IDENT NO. 51518		DOCUMENT NUMBER		
		SHEET 1 OF 1		SIZE A		000-1927-00