

Humidity and Temperature Wall Mount Transducers, SCT Series Product Nomenclature



For example, **SCTHWA43SDS** defines an SCT Series humidity and temperature transducer, wall mount, 4 mA to 20 mA output, 4 %RH humidity accuracy, 0.3 °C temperature accuracy/output type, -5 °C to 55 °C temperature range, LCD display, silver cover trim.

SCT	H	W	A	4	3	S	D	S
Series	Model Type	Installation Type	Output Type	Humidity Accuracy	Temperature Accuracy/Output Type	Temperature Range	LCD Display	Cover Trim Color
SCT Series Humidity and Temperature Wall Mount Transducers	H Humidity and temp.	W Wall mount	A Humidity: 4 mA to 20 mA Temperature: 4 mA to 20 mA	4 4 %RH	3 0.3 °C	S -5 °C to 55 °C [23 °F to 131 °F]	D LCD display	S Silver
	T Temperature		B Humidity: 0 V to 10 V Temperature: 0 V to 10 V	N None, temperature only	E NTC 10 kOhm		N No LCD display	G Gold
			C Humidity: 4 mA to 20 mA Temperature: passive		F NTC 20 kOhm	N None, temperature passive		
			D Humidity: 0 V to 10 V Temperature: passive		G Pt1000 Class A			
			E Temperature: 4 mA to 20 mA					
			F Temperature: 0 V to 10 V					