

MICRO SWITCH PK 8119 O

HEAVY DUTY LS LIMIT SWITCH WITH GOLD PLATED CONTACTS

— CAUTION —

This switch is designed to carry electrical loads given under Electrical Ratings **A** and **B** (see chart). However, if the switch is used at the higher current levels (Electrical Rating **A**), the gold plating will burn off the contacts. The switch will then no longer be reliable for low energy loads (Electrical Rating **B**).

* For switches with indicator light, use only at voltage stated for indicator light.

ELECTRICAL RATINGS

Circuits on any one pole must be same polarity.

10 amps. Continuous Carry

PILOT DUTY 600 VAC - 720 VA 240 VDC - 30 WATTS							
	AC VOLTS	CURRENT 0.35 POWER FACTOR		DC VOLTS	MAKE AND BREAK AMPS		
		AMPS			INDUCTIVE	RESISTIVE	
		MAKE	BREAK				
A*	120	60	6.0	A	120	0.25	0.8
	240	30	3.0		240	0.15	0.4
	480	15	1.5				
	600	12	1.1				
ELECTRONIC DUTY RATED							
B =	Electronic Duty - 5 VAC or VDC .01 amp (Recom. min. load)						

MICRO SWITCH

FREEPORT, ILLINOIS 61032

A DIVISION OF HONEYWELL

IN CANADA: 740 Eilemere Road, Scarborough, Ontario. INTERNATIONAL: Sales and service offices in all principal cities of the world.

PK8119 O 1276 PRINTED IN USA