

# MICRO SWITCH™ GSX Hazardous Area Switch Product Nomenclature

For example, a **GSXA01B** part number would define a GSX Series Hazardous Area Switch with 1/2-14 NPT conduit threads, a top pin plunger, and snap action 1NC 1NO circuitry.



GSX	A	01	B			-
Switch Type	Conduit Connection	Circuitry	Head Style	Actuator Style	Lever Roller	Modifications/ Specials
<b>GSX Series Hazardous Area Safety Switch</b>	<b>A</b> 1/2 in NPT	<b>01</b> Snap action, 1NC/1NO	<b>A</b> Side rotary; momentary	<b>1</b> Fixed length roller	<b>A</b> 19,0 mm x 6,35 mm [0.75 in x 0.25 in] nylon roller	<b>1</b> Clockwise rotation
	<b>B</b> PG 13.5	<b>03</b> Slow action, 1NC/1 NO, BBM	<b>B</b> Top pin plunger	<b>3</b> Yoke roller	<b>C</b> 24,4 mm x 12,7 mm [1.0 in x 0.5 in] nylon roller	<b>2</b> Counter-clockwise rotation
	<b>C</b> 20 mm	<b>04</b> Slow action, 1NC/1 NO, MBB	<b>C</b> Top roller plunger	<b>5</b> Offset roller	<b>D</b> 38,1 mm x 6,35 mm [1.5 in x 0.25 in] nylon roller	<b>3</b> Head assembled with actuator to right side
		<b>05</b> Slow action, 2NO	<b>D</b> Top roller lever		<b>E</b> 19,0 mm x 6,35 mm [0.75 in x 0.25 in] bronze roller	<b>4</b> Head assembled with actuator to left side
		<b>06</b> Slow action, 2NC			<b>W</b> 40 mm x 12,7 mm [1.5 in x 0.5 in] bronze roller	<b>5</b> Head assembled with actuator to mounting surface
		<b>07</b> Snap action, 1NC/1NO, gold contacts			<b>Y</b> 50,9 mm x 12,7 mm [2.0 in x 0.5 in] rubber roller	<b>6</b> Roller perpendicular to mounting surface
		<b>20</b> Snap action, 2NC/2NO				
		<b>22</b> Snap action, 2NC/2NO, gold contacts				
		<b>33</b> Slow action, 1NC/1NO, BBM				
		<b>34</b> Slow action, 1NC/1NO, MBB, gold contacts				
		<b>35</b> Slow action, 2NO, gold contacts				
		<b>36</b> Slow action, 2NC, gold contacts				
		<b>40</b> Slow action, 4NC				
		<b>41</b> Slow action, 4NC, gold contacts				
		<b>42</b> Slow action, 2NC/1NO, BBM				
		<b>43</b> Slow action, 2NC/1NO, BBM, gold contacts				
		<b>44</b> Slow action, 2NC/2NO, BBM				
		<b>45</b> Slow action, 2NC/2NO, BBM, gold contacts				
		<b>46</b> Slow action, 3NC/1NO, BBM				
		<b>47</b> 2NO/2NC, center neutral, high fidelity contacts, 0.5 in tap				

NOTE: not all combinations of model code are available.  
Please contact your Honeywell provider/representative for assistance.